



Decentralized Smart Modular Waste Processing and Management for Urban Communities

Mirtthyanthan Mukuntha Krishnan, Mohanlal Perumal

Coimbatore Institute of Engineering and Technology, Coimbatore, India

Publication History: Received: 25.02.2026; Revised: 20.03.2026; Accepted: 25.03.2026; Published: 28.03.2026.

ABSTRACT: Urban areas face waste issues due to lack of local disposal options, leading to dumping in vacant plots. This causes pollution, health risks, and loss of recyclables. This paper proposes a compact Decentralized Modular Waste Processing Hub that enables local segregation and processing of waste. The system integrates mechanical segregation, composting, and recyclable recovery. It reduces landfill dependence, transport cost, and improves cleanliness in dense communities.

KEYWORDS: Decentralized waste management, modular waste system, community waste processing, waste segregation, composting, resource recovery.

I. INTRODUCTION

Urban Waste Challenges: Rapid urbanization has significantly increased waste generation while reducing available land for management. In dense residential areas, the absence of accessible disposal systems often forces households to dump mixed waste in vacant plots, creating informal dumping sites characterized by foul odors, environmental pollution, and health risks.

The Failure of Centralized Models: Poor segregation practices lead to the loss of valuable recyclables and organic matter, complicating recovery efforts. Furthermore, centralized systems impose high operational costs due to long transportation distances and logistical inefficiencies.

The Decentralized Solution: To address these gaps, this paper proposes a compact, community-level decentralized hub as mandated by the Solid Waste Management Rules, 2016 [6]. Designed for a scalable capacity of 500 kg to 1 ton per day, the system functions as a "low-Waste" micro-infrastructure that:

- Integrates three-stage segregation (source, drop-point, and mechanical) to ensure high-purity input for downstream modules .
- Utilizes bio-mechanical aerobic composting within a constrained footprint of 1,200 sq. ft. to stabilize organic matter rapidly .
- Leverages an IoT-based monitoring framework (ESP32/GSM) to track parameters like temperature and moisture, ensuring process transparency and efficiency .

Project Objective: By replacing informal dumping sites with modular units powered by a 440V 3-phase supply, this solution aims to convert urban waste from a disposal problem into a manageable and recoverable local resource. The system is designed as a modular platform, allowing capacity and processing units to be adapted based on real-time waste composition of the community.

II. LITERATURE REVIEW

2.1 Centralized vs. Decentralized Models: Traditionally, urban waste management has relied on centralized systems. However, studies show these are inefficient in dense areas due to high transportation costs and land scarcity [1]. Decentralized approaches are increasingly suggested as a practical alternative to enable local processing and reduce environmental impact.

2.2 Material Recovery and Segregation: Material Recovery Facilities (MRFs) are widely used to improve recycling efficiency. Research indicates that proper source-level segregation significantly increases recovery rates and reduces contamination [2].



2.3 Organic Waste Processing: In-vessel composting systems—similar to the bio-mechanical aerobic unit proposed for this hub—have proven effective for processing organic waste in controlled environments while minimizing odor and emissions [3].

2.4 Modular Systems and IoT Integration: Recent developments highlight modular, small-scale units that improve operational flexibility and reduce dependency on centralized infrastructure [4]. Furthermore, the integration of IoT (e.g., ESP32/GSM) has enabled real-time monitoring and optimization of these processing systems [5].

2.5 Research Gap: Despite these advancements, a technical gap remains in integrating segregation, processing, and IoT monitoring into a single, compact (1,200 sq. ft.) system specifically designed for the constraints of dense urban neighborhoods .

III. SYSTEM DESIGN

3.1 Process Workflow

Process Workflow (The "Map")

The decentralized modular hub operates through a strictly defined linear progression, moving from source collection to final resource recovery. This "map" is designed to eliminate waste accumulation and maximize material purity at each stage.

1. **Primary Collection & Tri-Stream Intake:**
Waste arrives via manual push carts from the community.
Immediately separated at the inlet into three dedicated channels: Bio-waste, Plastics/Dry Recyclables, and E-waste .
2. **Mechanical Segregation & Pre-processing:**
Conveyor Feed: Dry waste is loaded onto a variable-speed belt for initial inspection.
Magnetic Separation: A suspended magnetic overbelt automatically extracts ferrous metals (e.g., cans, nails) to protect downstream machinery .
Trommel Screening: A rotating sieve filters the waste by size, separating fine organic residues from large-format plastics .
Manual Quality Control (QC): A final human-led check removes hazardous "rejects" (e.g., glass shards, medical waste) before secondary processing .
3. **Modular Secondary Processing:**
Organic Stream: Mixed with high-activity microbial inoculum and diverted to the bio-mechanical aerobic composter for rapid stabilization .
Plastic Stream: Directed to a dual-shaft shredder for size reduction (10–15mm flakes) followed by vertical densification into stackable blocks .
E-waste Stream: Transferred directly to fire-safe, weather-proof storage bins for periodic professional collection .
4. **Resource Output & Monitoring:**
Fertilizer Packaging: Stabilized compost is sieved and bagged for local community sale.
Data Logging: IoT-enabled load cells and sensors (ESP32-based) record the volume of waste processed and update a public-facing transparency dashboard.[1-5]

3.2 Mechanical & Biological Modules

This section details the ruggedized hardware required to process 1 ton/day within the 1,200 sq. ft. urban footprint.

1. Biological Module (Organic Waste)

- **Bio-Mechanical Aerobic Composter:** A horizontal, stainless steel (SS-304) insulated drum equipped with an internal ribbon agitator. It uses a gearbox-driven motor to provide continuous aeration and mixing .
- **Heating & Culture System:** Integrated ceramic heaters maintain a thermophilic temperature of 60°C–70°C. This is critical for ensuring pathogen reduction and stable compost output[7].
- **Leachate Management:** A sloped floor leads to a 200-liter HDPE collection tank. The leachate is passed through a sand-and-gravel filter before being recirculated into the composter (to maintain moisture) or discharged safely .

2. Mechanical Module (Inorganic Waste)

- **High-Intensity Magnetic Overbelt:** A permanent ferrite magnet suspended 200mm above the conveyor. It automatically extracts ferrous contaminants to protect the shredder blades from "abuse" or accidental metal intake .
- **Dual-Shaft Shredder:** A low-speed, high-torque machine (approx. 10 HP) designed to handle mixed plastics with durability against accidental hard waste inputs.



- Vertical Hydraulic Densifier: A compact press that applies 10–15 tons of pressure to shredded flakes, reducing plastic volume by up to 80% into stackable 20kg blocks [8].
3. Environmental Safety Hardware
- Multi-Stage Air Filtration: To prevent odors in dense neighborhoods, the bio-zone uses a centrifugal blower to pull air through:
 - Bio-filter: Bark/woodchip media for ammonia removal.
 - Activated Carbon Scrubber: For VOC and tobacco odor neutralization.
 - HEPA Filter: To trap micro-plastic dust from the shredding module .

3.3 IoT & Control Architecture

Instead of specifying hardware like the ESP32, this section now focuses on the logic and functional capabilities required to manage the hub's unique waste streams.

1. Modular Control Logic:

- System Controller: The hub uses a programmable industrial-grade microcontroller or PLC (Programmable Logic Controller) capable of processing multiple sensor inputs simultaneously.
- Fail-Safe Protocols: The controller is programmed with an Auto-Reverse Sequence. If the sensors detect a current spike in the mechanical shredder (indicating a jam from "hard" waste), the system automatically reverses the motor to clear the blades, preventing mechanical failure.

2. Dynamic Process Monitoring:

- Thermal Regulation: High-precision temperature probes monitor the bio-mechanical reactor. The system maintains a thermophilic range (60°C–70°C), which is essential for ensuring pathogen reduction and stable compost output[7].
- Moisture Feedback Loop: Automated sensors trigger a solenoid-controlled misting system using filtered leachate to maintain the ideal moisture levels for aerobic digestion.

3. Data Connectivity & Transparency:

- Telemetry: The system requires a dual-mode communication gateway (supporting both local Wi-Fi and Cellular/GSM) to transmit operational data to a central cloud server.
- Public Metrics: Load-sensing platforms (load cells) under the intake hoppers calculate the total tonnage processed. This data is pushed to an external digital display to show the community the real-time environmental impact (e.g., "Total Waste Diverted from Landfill").

IV. METHODOLOGY

The implementation follows a modular-integrated approach, beginning with the site preparation of a 1,200 sq. ft. compact layout within a dense urban neighborhood. The hardware—comprising tri-stream intake hoppers, a magnetic separator, a dual-shaft shredder, and a bio-mechanical composter—is installed as independent, plug-and-play modules powered by a 440V 3-phase supply. The system is designed as a modular platform, allowing capacity and processing units to be adapted based on the real-time waste composition of the community.

Testing is conducted in three distinct phases:

1. Mechanical Stress Testing: To verify the Auto-Reverse Sequence and the durability of shredder blades against accidental hard waste inputs.
2. Biological Validation: Monitoring the reactor to ensure a consistent thermophilic range (60°C–70°C) for pathogen reduction and stable compost output.
3. Data Calibration: Testing the dual-mode communication gateway (Wi-Fi/GSM) and load cells to ensure accurate real-time data transmission to the public transparency dashboard.

V. FUTURE WORK

The proposed system will be further developed through detailed mechanical design and prototype fabrication. Future research includes testing in real-world urban environments to validate the system's performance in non-controlled, high-density settings. Key areas for optimization involve adjusting module parameters based on variable waste compositions and increasing automation levels through advanced sensor fusion and machine learning.

Additionally, the system will explore scalable deployment across multiple locations and seamless integration into municipal smart city networks. Subsequent research will investigate advanced recycling methods such as pyrolysis or chemical upcycling and focus on design optimization to support patent applications for proprietary modular solutions.



VI. CONCLUSION

The proposed decentralized modular waste processing hub offers a technically viable and scalable solution for managing solid waste in dense urban environments. By integrating three-stage segregation, bio-mechanical aerobic composting, and vertical plastic densification into a compact 1,200 sq. ft. footprint, the system addresses the primary inefficiencies of centralized waste models—namely high transportation costs and land scarcity [1].

Key expected outcomes include:

Operational Efficiency: Maintaining a thermophilic range of 60°C–70°C helps ensure rapid pathogen reduction and stable compost output, even when handling complex household organic streams [7].

Volume Optimization: The mechanical module is designed to reduce plastic waste volume by up to 80%, facilitating easier storage and transport within constrained urban spaces [8].

Transparency: The integration of a dual-mode IoT framework (Wi-Fi/GSM) provides real-time data logging, fostering community trust and reducing the likelihood of site abuse.

By converting informal dumping sites into managed, resource-recovery micro-infrastructures, this model aligns with the Solid Waste Management Rules (2016) [6] and provides a practical roadmap for urban local bodies to achieve localized waste circularity.

REFERENCES

1. Kaza, S., et al. (2018). What a Waste 2.0: A Global Snapshot of Solid Waste Management. World Bank.
2. Wilson, D. C., et al. (2015). Global Waste Management Outlook. UNEP.
3. Zhang, D., et al. (2014). In-vessel composting of organic waste. Waste Management Journal.
4. UNEP (2021). Waste Management Outlook for Cities.
5. Aljerf, L. (2018). Smart waste management using IoT.
6. Ministry of Environment, Forest and Climate Change. (2016). Solid Waste Management Rules, 2016. Government of India Gazette.
7. Central Pollution Control Board (CPCB). (2017). Guidelines for Composting and Management of Municipal Solid Waste. International Journal of Engineering Research & Technology (2020). Plastic Waste Densification Techniques.
8. C.Nagarajan and M.Madheswaran - 'Stability Analysis of Series Parallel Resonant Converter with Fuzzy Logic Controller Using State Space Techniques'- Taylor & Francis, Electric Power Components and Systems, Vol.39 (8), pp.780-793, May 2011. DOI: 10.1080/15325008.2010.541746
9. C.Nagarajan and M.Madheswaran - 'Experimental verification and stability state space analysis of CLL-T Series Parallel Resonant Converter' - Journal of Electrical Engineering, Vol.63 (6), pp.365-372, Dec.2012. DOI: 10.2478/v10187-012-0054-2
10. C.Nagarajan and M.Madheswaran - 'Performance Analysis of LCL-T Resonant Converter with Fuzzy/PID Using State Space Analysis'- Springer, Electrical Engineering, Vol.93 (3), pp.167-178, September 2011. DOI 10.1007/s00202-011-0203-9
11. S.Tamilselvi, R.Prakash, C.Nagarajan, "Solar System Integrated Smart Grid Utilizing Hybrid Coot-Genetic Algorithm Optimized ANN Controller" Iranian Journal Of Science And Technology-Transactions Of Electrical Engineering, DOI10.1007/s40998-025-00917-z,2025
12. S.Tamilselvi, R.Prakash, C.Nagarajan, " Adaptive sliding mode control of multilevel grid-connected inverters using reinforcement learning for enhanced LVRT performance" Electric Power Systems Research 253 (2026) 112428, doi.org/10.1016/j.epsr.2025.112428
13. S.Thirunavukkarasu, C. Nagarajan, 2024, "Performance Investigation on OCF and SCF study in BLDC machine using FTANN Controller," Journal of Electrical Engineering And Technology, Volume 20, pages 2675–2688, (2025), doi.org/10.1007/s42835-024-02126-w
14. C. Nagarajan, M.Madheswaran and D.Ramasubramanian- 'Development of DSP based Robust Control Method for General Resonant Converter Topologies using Transfer Function Model'- Acta Electrotechnica et Informatica Journal , Vol.13 (2), pp.18-31, April-June.2013, DOI: 10.2478/aei-2013-0025.
15. C.Nagarajan and M.Madheswaran - 'DSP Based Fuzzy Controller for Series Parallel Resonant converter'- Springer, Frontiers of Electrical and Electronic Engineering, Vol. 7(4), pp. 438-446, Dec.12. DOI 10.1007/s11460-012-0212-0.



16. C.Nagarajan and M.Madheswaran - 'Experimental Study and steady state stability analysis of CLL-T Series Parallel Resonant Converter with Fuzzy controller using State Space Analysis'- Iranian Journal of Electrical & Electronic Engineering, Vol.8 (3), pp.259-267, September 2012.
17. C.Nagarajan and M.Madheswaran, "Analysis and Simulation of LCL Series Resonant Full Bridge Converter Using PWM Technique with Load Independent Operation" has been presented in ICTES'08, a IEEE / IET International Conference organized by M.G.R.University, Chennai.Vol.no.1, pp.190-195, Dec.2007
18. Suganthi Mullainathan, Ramesh Natarajan, "An SPSS and CNN modelling based quality assessment using ceramic materials and membrane filtration techniques", Revista Materia (Rio J.) Vol. 30, 2025, DOI: <https://doi.org/10.1590/1517-7076-RMAT-2024-0721>
19. M Suganthi, N Ramesh, "Treatment of water using natural zeolite as membrane filter", Journal of Environmental Protection and Ecology, Volume 23, Issue 2, pp: 520-530,2022
20. Vimal, V. R., & Banerjee, J. S. (2025). Integrating PSO, GA, and ACO for Optimized ECG Feature Selection and Classification of Cardiac Disorders. SGS-Engineering & Sciences, 1(5).
21. Gopinathan, V. R. (2023). Cloud-First AI Security Architecture for Protecting Enterprise Digital Ecosystems and Financial Networks. International Journal of Research and Applied Innovations, 6(6), 10031-10039.
22. Mathew, A. A Secure, Trustworthy, and Regulated Framework for AI Agents in Distributed Networks.
23. Anbazhagan, K. (2025). Secure AI Enabled Enterprise Ecosystems for Fraud Prevention Compliance Automation and Real Time Analytics. International Journal of Multidisciplinary Research in Science, Engineering, Technology & Management, 1(4), 6-13.
24. Soundappan, S. J. (2026). Building Trustworthy AI: Explainability and Security in Modern Cloud-Native Data-Driven Ecosystem Platforms. International Journal of Engineering & Extended Technologies Research (IJEETR), 8(2), 570-579.
25. Sugumar, R. (2025). Cyber-Secure Cloud Architecture Integrating Network and API Controls for Risk-Aware SAP Healthcare Data Platforms. International Journal of Humanities and Information Technology, 7(4), 53-60.
26. Vimal, V. R., & Banerjee, J. S. (2025). Integrating PSO, GA, and ACO for Optimized ECG Feature Selection and Classification of Cardiac Disorders. SGS-Engineering & Sciences, 1(5).
27. Gopinathan, V. R. (2025). AI-Powered Kubernetes Orchestration for Complex Cloud-Native Workloads. International Journal of Research Publications in Engineering, Technology and Management (IJRPETM), 8(6), 13215-13225.
28. Mathew, A. From Conversation to Command Execution: A Comparative Threat Modeling and Risk Analysis of OpenClaw and ChatGPT. Risk, 100(1).
29. Inbavalli, M., & Arasu, T. (2015). Efficient Analysis of Frequent Item Set Association Rule Mining Methods. International Journal of Scientific & Engineering Research, 6(4).
30. Sugumar, R. (2025). Secure and Explainable AI Systems in Cloud-Based Applications: Bridging Trust and Performance. *International Journal of Engineering & Extended Technologies Research (IJEETR)*, 7(4), 10328-10335.
31. Rajasekar, M. (2025). Risk-Aware Generative AI and Machine Learning Frameworks for Privacy-Preserving Banking and Trade Analytics over Cloud and 5G Networks. *International Journal of Computer Technology and Electronics Communication*, 8(4), 11078-11086.
32. Gopalakrishnan, S., Dhinakaran, D., Raja, S. E., Raghavan, P., & Girija, M. S. (2026). Fusion-Driven Medical Image Encryption Framework with Entropy-Calibrated Control and Integrity Assurance. *KSII Transactions on Internet & Information Systems*, 20(2).
33. G. Vimal Raja, K. K. Sharma (2014). Analysis and Processing of Climatic data using data mining techniques. *Envirogeochemica Acta 1 (8):460-467*.
34. Soundappan, S. J. (2020). Big Data Analytics in Healthcare: Applications for Pandemic Forecastin. *International Journal of Advanced Research in Computer Science & Technology (IJARCST)*, 3(1), 2248-2253.
35. Aarthi, K., Thirumoorthy, P., Tamizharasu, K., Manoja, R., Kalyanasundaram, P., & Rajasekar, M. (2025, September). Improved Network lifetime using Cluster based Power-Aware Balanced Routing Protocol for Device to Device Communication. In *2025 6th International Conference on Electronics and Sustainable Communication Systems (ICESC)* (pp. 1005-1010). IEEE.
36. Mathew, A. Cybersecurity 5.0: From Firewalls to Fully Autonomous Digital Protection.
37. Rengarajan, A. (2025). Cloud-Based AI-Driven Threat Detection Framework for Smart Grid Cybersecurity. *International Journal of Future Innovative Science and Technology (IJFIST)*, 8(6), 16065.
38. Anbazhagan, K. (2025). Next-Generation Enterprise Cloud AI for Healthcare: Secure CNN Pipelines and Privacy Controls. *International Journal of Future Innovative Science and Technology (IJFIST)*, 8(6), 15980.